

SQID COMPANY

600 SQID®

Storm Water Management Systems

SQID COMPANY
Pty Ltd
ACN137578951

Other products
manufactured &
supplied by
SQID COMPANY
Pty Ltd:

Storm Water
Management Systems:

SQID®
450 x 450
600 x 600
900 x 600
900 x 600 RE
900 x 900 (2 Pt)

InFil-trator 450

Water Treatment
Systems:

Storm Water Reuse
HydroFil 3500

Distributed by:
AUSDRAIN
Stormwater Solutions



10/2 Bells Avenue
Camberay NSW 2062
Ph. 02 9929 7650
Fax. 02 9929 7655
Toll free 1300 287 372
www.ausdrain.com

Model: 46060A with installation kit (inside pit).

Model: 46060B with installation kit (inside pit).



The 46060 Model SQID®

The SQID® is a pit insert for the primary treatment of storm water at the source. This SQID® is for use in car-parks, industrial driveways, gardens and court yards. Applications are also applicable in some high-density, urban developments with medium requirements.

The range of SQID® are manufactured from UV stabilised polyethylene and fitted with stainless steel mesh screens.

The SQID® design ensures that all gross pollutants and waste is prevented from entering the storm water drains to reduce adverse impacts on the environment.

SQID COMPANY 600 Sqid®

Unique features

- ◆ No moving/ wearing parts.
- ◆ Removes all sediment and litter over 2mm particle size.
- ◆ Solid and durable, long life expectancy and is UV stable.
- ◆ Dry cell principals.
- ◆ Can be retro-fitted to existing pits.
- ◆ At the source solution.
- ◆ Cost effective and efficient.
- ◆ Land fill disposal for sediment/ litter collection.
- ◆ Treatment rate tested to a maximum 60 litres per second.
- ◆ Substantial by-pass capabilities up to 15 litres per second.



The SQID® 600 Range

46060A model is trimmed to 600x 600 to fit inside the walls of a 600 pit. And will require a Sqid Kit which comes complete with an installation kit and instructions.

46060B model is trimmed to 635x635 and is designed to fit under the grate of pits with rebates for their grates.

Both models are 225mm deep and have the treatment rates and by-pass levels.

NB. Specifications are subject to change.

Your Local Distributor:



Installation Instructions

- ◆ For removal of the insert, a clear opening greater than the insert is required. Inserts are manufactured to the nominal sizes indicated in the range.
- ◆ To install the SQID® 46060A Kits are available. The kit consists of 3mm aluminium angle, 25mm x 25mm fastened to the pit wall below the grate.
- ◆ Installation of the 46060B is as simple as lifting the grate and placing the SQID® on the grate rebate. (There are some pits which will require the SQID® to be trimmed).

Recommended Maintenance

Inspection after each major rain event.

Care should be taken when manual lifting is applied.

